



Softbreath Vapor permeable 180GSM

Datasheet

Quality Covers Softbreath is a self-adhesive and slightly breathable covering material.

The vapor-permeable film allows moisture to pass through from the underside, while the top side remains completely liquid-proof.

| Specifications | |
|-------------------------|---|
| M ² per roll | 0,67m x 37,3m= 25m ² 1m x 25m 1m x 50m |
| Grammage | 180 gr/m ² |
| Vapor permeability | 122 gr/ 24 hours / m ² |
| Packaging | Packed in plastic bags, in box, on wooden europallets |
| Color | Blue |
| Usability | Max. 1 month (up to 40°C) |
| Storage | Dry and protected from moisture, preferably in the original packaging |
| Shelf life | Max. 12 months (at room temperature, store in a dry place) |

Area of application

- Freshly laid ceramic tile floors
- Freshly bonded wood, parquet and laminate flooring
- Non-flat subfloors such as stairs
- Indoor use

Properties

- Vapor permeable
- Liquid-proof
- Self-adhesive
- Leaves no glue residues
- Shock-absorbing



Softbreath Vapor permeable 180GSM

Datasheet

Application

- The substrate must be dry, clean and dust-free
- Switch off the underfloor heating
- Lay the product flat on the subfloor with the self-adhesive side facing downwards
- Overlap by 10 cm
- Always test beforehand whether the product is suitable for the substrate

Notes

Softbreath is not resistant to aggressive substances; the substrate must be permanently dry, clean and free of dust and solvents. If the breathable fleece is damaged, it must be replaced.

Our application recommendations are to support the buyer or processor and are based on our testing and experience. You are responsible for checking the suitability for the intended purpose, for example by testing on a small area. The manufacturer assumes no liability for any damage that may occur. No rights can be derived from this data sheet. Kwabo Techniek B.V. reserves the right to make technical changes and developments.



Softbreath Vapor permeable 160GSM

Datasheet

Quality Covers Softbreath is a self-adhesive and slightly breathable covering material.

The vapor-permeable film allows moisture to pass through from the underside, while the top side remains completely liquid-proof.

| Specificaties | |
|-------------------------|---|
| M ² per roll | 0,67m x 37,3m= 25m ² 1m x 25m 1m x 50m |
| Grammage | 160 gr/m ² |
| Vapor permeability | 233 gr/ 24 hours / m ² |
| Packaging | Packed in plastic bags, in box, on wooden europallets |
| Color | Blue |
| Usability | Max. 1 month (up to 40°C) |
| Storage | Dry and protected from moisture, preferably in the original packaging |
| Shelf life | Max. 12 months (at room temperature, store in a dry place) |

Area of application

- Freshly laid ceramic tile floors
- Freshly bonded wood, parquet and laminate flooring
- Non-flat subfloors such as stairs
- Indoor use

Properties

- Vapor permeable
- Liquid-proof
- Self-adhesive
- Leaves no glue residues
- Shock-absorbing



Softbreath Vapor permeable 160GSM

Datasheet

Application

- The substrate must be dry, clean and dust-free
- Switch off the underfloor heating
- Lay the product flat on the subfloor with the self-adhesive side facing downwards
- Overlap by 10 cm
- Always test beforehand whether the product is suitable for the substrate

Notes

Softbreath is not resistant to aggressive substances; the substrate must be permanently dry, clean and free of dust and solvents. If the breathable fleece is damaged, it must be replaced.

Our application recommendations are to support the buyer or processor and are based on our testing and experience. You are responsible for checking the suitability for the intended purpose, for example by testing on a small area. The manufacturer assumes no liability for any damage that may occur. No rights can be derived from this data sheet. Kwabo Techniek B.V. reserves the right to make technical changes and developments.